

SPECIAL FEATURES

The ORION 8ch CSDRP8 distributor & repeater is a distance extension device for HD-SDI. In addition, there are two outputs from one input. Therefore, user can use eight monitors with one HD-CCTV camera. When user uses repeater between HD-CCTV and Receiver, the distance can be increased 100M per repeater.

- 1 channel (HD-SDI) Input
- 8 channels (HD-SDI) Output - Signal Distribution
- 100M Signal Amplify
- Each Additional RP-102S Increase the Transmission Distance 100M
- DC12V 500mA or more
- 5C-HFBT Type Impedance Coaxial Cable


SPECIFICATIONS

CSDRP8 Repeater		
Video	Input	1ch / HD-SDI (BNC type)
	Output	8ch / HD-SDI (BNC)
Resolution	Input	1920 x 1080p (60/59.94/50/30/29.97/25)Hz
		1920 x 1080i (60/59.94/50)Hz
		1280 x 720p (60/59.94/50)Hz
	Output	1920 x 1080p (60/59.94/50/30/29.97/25)Hz
		1920 x 1080i (60/59.94/50)Hz
Power	Electrical Rating	12V DC (+/-2V) / 200mA +/- 10%
	Consumption < On	Max 6W
Mechanical	Weight (lbs)	603g (1.32 lbs)
	Dimension (inch)	8.03" x 1.25" x 3.36"
Circumstance	Operating Temperature	-10° C ~ 60° C
	Humidity	30% ~ 80% RH


*Design and specifications are subject to change without notice

DIMENSIONS

CSDRP8 Repeater



CONFIGURATION



OTHER VIEW

